

Indoor Splitter 2 Way, 3 Way, 4 Way

2-way Splitter 2812A



3-way Splitter 2813A



4-way Splitter 2814A

Features :

- ★ Zinc alloy die casting shell with tin or nickel plated surface treatment.
- ★ Adopt complete tin sealed design, shield level: 5-1000MHz \geq 100dB.
- ★ two way transmission design.
- ★ Easy installation, two side holes are used for fixing the main unit.
- ★ Surface spray-paint treatment, anti-oxidation and no color fading.

ITEMS		MODEL		
	Frequency Range (MHz)	2812A	2813A	2814A
Insertion Loss (dB)	5-10 MHz	\leq 3.5	\leq 5.7	\leq 6.8
	10-50 MHz	\leq 3.6	\leq 5.5	\leq 7.0
	50-750 MHz	\leq 3.8	\leq 6.2	\leq 7.6
	750-1000 MHz	\leq 4.0	\leq 6.5	\leq 8.0
Isolation (dB)	5-10 MHz	\geq 25	\geq 22	\geq 27
	10-50 MHz	\geq 28	\geq 25	\geq 28
	50-750 MHz	\geq 28	\geq 25	\geq 28
	750-1000 MHz	\geq 25	\geq 22	\geq 25
Return Loss (dB)	5-10 MHz	\geq 16	\geq 16	\geq 16
	10-50 MHz	\geq 18	\geq 18	\geq 18
	50-750 MHz	\geq 18	\geq 18	\geq 18
	750-1000 MHz	\geq 16	\geq 16	\geq 16